UDC 539.219.3

MATHEMATICAL METHODS OF THE INTERMEDIATE PHASE GROWTH DESCRIBING

Yarmolenko M. V., PhD in Physics and Mathematics, Associate Professor

Kyiv National University of Technologies and Design, Ukraine, Cherkasy

A model of describing the diffusion phase growth from point sources inside polycrystals grains is regarded. Analytical method to solve differential diffusion equations for such model is suggested. Analytical method to solve differential diffusion equations of describing the growth of the phase wedge during the intermetallic compound formation with a narrow concentration range of homogeneity in bicrystals is proposed. Parabolic, cubic, fourth power diffusion regimes for different scales from nanometers to micrometers and millimeters are analyzed.

Key words: diffusion, reaction, phase growth law, intermetallic compounds, grain boundaries.

кандидат фізико-математичних наук, доцент Ярмоленко М. В. Математичні методи опису росту проміжної фази / Київський національний університет технологій та дизайну, Україна, Черкаси

Розглядається модель, яка описує кінетику утворення інтерметалевої фази джерела всередині 3 точкового полікристалічних зерен. Пропонується відповідний аналітичний метод розв'язування диференціального рівняння такої моделі. Пропонується аналітичний метод розв'язування диференціального рівняння, яке описує кінетику утворення інтерметалевої фази вздовж границі між зернами з одночасним проникненням у самі зерна. Аналізуються дифузійні режими (параболічний, кубічний,

четвертого степеня) для різних масштабів: від нанометрового до мікрометрового і міліметрового.

Ключові слова: дифузія, реакції, закон росту фази, інтерметалеві сполуки, міжфазні границі.

кандидат физико-математичних наук, доцент Ярмоленко М. В. Математические методы описания роста промежуточной фазы / Киевский национальный университет технологий и дизайна, Украина, Черкассы

Рассматривается модель, которая описывает кинетику образования интерметаллического соединения из точечного источника внутри поликристаллических зерен. Предлагается соответствующий аналитический метод решения дифференциального уравнения такой модели. Предлагается аналитический метод решения дифференциального уравнения, которое описывает кинетику образования интерметаллического соединения вдоль границы между зернами с одновременным проникновением в сами зерна. Анализируются диффузионные режимы (параболический, кубический, четвертой степени) для разных масштабов: от нанометрического до микрометрического и миллиметрового.

Ключевые слова: диффузия, реакции, закон роста фазы, интерметаллические соединения, межфазные границы.

1. Introduction

The Kirkendall effect and phase formation kinetics during solid state reactions were analyzed in [1] using experimental results in the diffusion region of Zn-Cu alloy. This system has several intermediate phases : β -brass, concentration of Zn is about 50%; γ -brass, concentration of Zn is about 68%; ϵ -brass, concentration of Zn is about 84%. These phases are

formed between α-brass and Zn during diffusion. Approximation of constant diffusion flux along the diffusion direction within the width of each phase is used (so-called constant flux method) for describing the growth kinetics of the phases which was theoretically grounded in [2]. This technique necessitates no allowance for the concentration dependence of D(C). Deviations from the parabolic law of phase growth in cylindrical and spherical samples were analyzed in [3] using this method. This method was applied for describing the growth kinetics of thin γ-brass and ε-brass layers in a cylindrical sample at 400°C (Cu was in the centre of the cylindrical specimens). The γ-brass layer grew slower and the ε-brass layer grew more rapidly than in the planar sample [4]. Model of the growth of an intermediate phase between low-soluble components on diffusion at grain boundaries involving outflow was suggested in [5] and criteria for a transition from the Fisher regime t^{1/4} to a parabolic one were established. It was proved in [6] that perpendicular grain boundaries do not influence phase growth kinetics in B-regime. This result allows us to use the wellknown model of a polycrystal as a 3-D array of grain boundaries to be perpendicular to the interface for describing the phase growth. There were no explanations in [5] and [6] how one can solve differential diffusion equations because of a very complicated method. The formalism suggested was extended to the case of the growth of a solid-state solution with an exponential concentration dependence of the diffusion coefficient. Analytical solution and Monte Carlo modeling of the Kirkendall effect were suggested in [7]. Grain boundary diffusion parameters determination using A-Kinetics of intermetallic layer formation was proposed Experimental data on Cu₅Zn₈ (y-brass) diffusion growth kinetics were used in [8] and [9] for separate determination of the volume diffusion activation enthalpy and the GB activation enthalpy. One can improve the methods to solve the diffusion equations for the growth of intermediate phase in bicrystals, polycrystals and inside grains.

2. Models and methods

- MODEL 1. A model of the phase layer growth during the intermetallic compound formation with a narrow concentration range of homogeneity inside grains is based on the following assumptions:
- 1. An intermediate phase 1 forms inside grains from a point source of substance A that is surrounded by substance B. The point source has a diameter of $\delta \approx 1$ nm. The dislocations steps can be the point sources in nanometers scale.
- 2. Dislocation pipe is easy path for A-atoms to go from substance A to the dislocations steps with a diffusion coefficient $D_d \approx D_b$ and a diameter of $\delta \approx 1$ nm.
- 3. Formed spherical phases 1 broadens in 3-D space from the dislocations steps due to diffusion with a diffusion coefficient D_1 ($D < D_1 < D_d$).

METHOD 1. One can use constant flux method [3] to get differential equation for intermetallic compound growing inside polycrystals grains from a point source and forming small spherical particles:

$$J_{sph} = \frac{4\pi \frac{\delta}{2} R(t) D_1 \Delta C_1}{R(t) - \frac{\delta}{2}} = 4\pi R^2(t) C_1 \frac{dR(t)}{dt} , \quad R(t) >> \frac{\delta}{2}$$
 (1)

or
$$\frac{dR(t)}{dt}R^{2}(t) = \frac{D_{1}\Delta C_{1}}{2C_{1}}\delta$$
 (2)

and the solution
$$R(t) = \sqrt[3]{\frac{3D_1 \Delta C_1 \delta}{2C_1}} \sqrt[3]{t} \ .$$

(3)

- MODEL 2. The model of the phase layer growth during the intermetallic compound formation with a narrow concentration range of homogeneity, ΔC_1 , in bicrystals is based on the following assumptions [5], [6]:
- 1. An intermediate phase forms at first on the basis of the grain boundary (GB); the latter, transforming from the boundary A-A to the boundary 1-1, remains, due to easy influx with a diffusion coefficient D_b and having a thickness of $\delta \approx 1$ nm (i.e., the GB is not overgrown with a new phase and does not bifurcate).
- 2. Formed phase 1 broadens normal to the GB due to volume diffusion with a diffusion coefficient $D << D_b$.
- 3. At all the points of the formed 1-A phase boundary between the broadening phase 1 and the matrix A the concentration of the component B is C_1 on the side of phase 1 and is zero on the side of phase A (solubility of B in A is ignored).
- 4. Outflow from the GB is the same at all GB points:

$$\frac{\partial C}{\partial x} = \frac{\Delta C(x)}{x(t,y)} = \frac{\Delta C_1}{x(t,0)} ; \qquad x(t,0) = \sqrt{\frac{2D\Delta C_1}{C_1}} \sqrt{t} . \tag{4}$$

5. A flow in the volume of a phase wedge normal to the GB is constant along x (a corresponding property is proved in [2]) in a reference system associated with the moving nose of the wedge, y(t).

The equation for y(t) has such form [5], [6]:

$$\frac{dy(t)}{dt} = \frac{A}{y(t)} - B\frac{y(t)}{\sqrt{t}},\tag{5}$$

where
$$A=rac{D_b\Delta C_1}{C_1}$$
 , $B=rac{1}{\mathcal{S}}\sqrt{rac{2D\Delta C_1}{C_1}}$.

There were no explanations in [5] and [6] how equation (5) can be solved as a very complicated method was used. A simpler method can be pointed out.

METHOD 2. One can simplify equation (5) by the following way

$$\frac{dz(t)}{dt} = 2A - \frac{2B}{\sqrt{t}}z(t), \qquad (6)$$

where

$$z(t) = u(t)v(t) = y_0^2(t)$$
.

One can transform equation (6) into

$$\frac{du(t)}{dt}v(t) + u(t)\left(\frac{dv(t)}{dt} + \frac{2B}{\sqrt{t}}v(t)\right) = 2A . \tag{7}$$

Assumption
$$\frac{dv(t)}{dt} + \frac{2B}{\sqrt{t}}v(t) = 0 \qquad \text{leads to} \quad v(t) = e^{-4B\sqrt{t}} \ .$$

Next step gives:

$$u(t) = 2A \int e^{4B\sqrt{t}} dt = \frac{A}{B} \sqrt{t} e^{4B\sqrt{t}} - \frac{A}{4B^2} e^{4B\sqrt{t}} + \frac{A}{B} C_0.$$
 (8)

General solution of equation (6) is as follows:

$$z(t) = \frac{A}{B}\sqrt{t} - \frac{A}{4B^2} + \frac{A}{B}C_0 e^{-4B\sqrt{t}}$$
 (9)

Using initial conditions z(t=0)=0 one can obtain finally

$$z(t) = \frac{A}{B}\sqrt{t} - \frac{A}{4B^2}(1 - e^{-4B\sqrt{t}})$$
(10)

or
$$y(t) = \sqrt{\frac{A}{B}\sqrt{t} - \frac{A}{4B^2}(1 - e^{-4B\sqrt{t}})}$$
 (11)

Equation (11) show the Fisher diffusion regime

$$y(t) = \sqrt[4]{\frac{D_b^2 \delta^2 \Delta C_1}{2DC_1}} \sqrt[4]{t}$$
 (12)

for

$$\sqrt{\frac{D_b}{2D}}\delta < y(t) < \frac{D_b}{2D}\delta.$$

3. Analysis

It was proved in [6] that perpendicular grain boundaries do not influence phase growth kinetics in B-regime. This result allows us to use the wellknown model of a polycrystal as a 3-D array of grain boundaries to be

perpendicular to the interface for describing the phase growth. The growth phase layer law in polycrystals for diffusion time

$$t_{\frac{1}{4} \to \frac{1}{2}} > \frac{D_b^2 C_1 \delta^2}{8D^3 \Delta C_1} \tag{13}$$

is parabolic because volume diffusion is more pronounced than GB diffusion.

Parabolic diffusion regime is valid in micrometers and millimeters scales [4]

for
$$y(t) > \frac{D_b}{2D} \delta$$
 [5], [6]:
$$y(t) = \sqrt{\frac{2D\Delta C_1}{C_1}} \sqrt{t} . \tag{14}$$

Parabolic diffusion regime is valid in nanometers scale and the growth

phase layer law is as follows:
$$y(t) = \sqrt{\frac{2D_b \Delta C_1}{C_1}} \sqrt{t} \ . \eqno(15)$$

A comparison of equations (3) and (15) show that

$$t_{\frac{1}{2} \to \frac{1}{3}} \approx \frac{C_1 \delta^2}{\Delta C_1} \sqrt{\frac{D_b^3}{2D^5}} . \tag{16}$$

One can find:
$$t_{\frac{1}{3} \to \frac{1}{4}} \approx \frac{D_b^2 C_1 \delta^2}{6D_1^3 \Delta C_1}$$
 and $y(t_{\frac{1}{3} \to \frac{1}{4}}) \approx \left(\frac{D_b}{2D_1}\right)^{\frac{2}{3}} \delta$ (17)

4. Summary

The growth law of the phase layer during the intermetallic compound formation with a narrow concentration range of homogeneity is parabolic for diffusion time $t < \frac{C_1 \delta^2}{\Delta C_1} \sqrt{\frac{D_b^3}{2D^5}}$. The growth phase layer law inside polycrystals grains is proportional to $\sqrt[3]{t}$ in about 100 nanometers scale for diffusion time $\frac{C_1 \delta^2}{\Delta C_1} \sqrt{\frac{D_b^3}{2D^5}} < t < \frac{D_b^2 C_1 \delta^2}{6D_1^3 \Delta C_1}$. The growth phase layer law in bicrystals in B-regime is the same as the Fisher solution: the phase wedge is proportional to $\sqrt[4]{t}$ for diffusion time $\frac{D_b^2 C_1 \delta^2}{6D_1^3 \Delta C_1} < t < \frac{D_b^2 C_1 \delta^2}{8D^3 \Delta C_1}$. The phase wedges and roughness are smoothed during phase growth [6], [4]. Smoothing rate is the more pronounced, the smaller the roughness radius [3], [10], [11]. The growth phase layer law in polycrystals in micrometers and millimeters scales for diffusion time $t > \frac{D_b^2 C_1 \delta^2}{8D^3 \Delta C_1}$ is parabolic because volume diffusion is more pronounced than GB diffusion.

References:

- 1. Yarmolenko M. V. The Kirkendall Effect and Phase Formation Kinetics during Solid State Reactions / M.V.Yarmolenko // Науковий огляд. 2018. №1 (44). С. 42 52.
- 2. Ярмоленко М. В. О постоянстве потока в растущем слое интерметаллида при взаимной диффузии / К. П. Гуров, А. М. Гусак, М. В. Ярмоленко // Металлофизика. 1988. Т.10, №5. С. 91 -92.
- 3. Yarmolenko M. V. A simple way of describing the diffusion phase growth in cylindrical and spherical samples / A. M. Gusak, M. V. Yarmolenko // Journal of Applied Physics. 1993. Vol.73, №10. P. 4881-4884.
- 4. Ярмоленко М. В. Особенности диффузионного роста фаз в образцах цилиндрической формы / В. В. Богданов, А. М. Гусак, Л. Н.

- Парицкая, М. В. Ярмоленко // Металлофизика. 1990. Т.12, №3. С. 60 - 66.
- 5. Yarmolenko M. V. A model of growth of an intermediate phase in biand polycrystals / M. V. Yarmolenko, A. M. Gusak, K. P. Gurov // Journal of Engineering Physics and Thermophysics. 1993. 65(3). P. 876 881.
- 6. Yarmolenko M. V. Describing the Diffusion Phase Growth in Polycrystals: Analytical Solution / M. V. Yarmolenko // Defect and Diffusion Forum. 1997. Vols. 143-147. P. 1567-1572.
- 7. Yarmolenko M. V. The Kirkendall Effect: Analytical Solution and Monte Carlo Modeling / M. V. Yarmolenko // Defect and Diffusion Forum. 1997. Vols. 143-147. P. 509-514.
- 8. Yarmolenko M. V. Grain Boundary Diffusion Parameters Determination using A-Kinetics of Intermetallic Layer Formation / M. V. Yarmolenko // Solid State Phenomena. 2000. Vol.72. P.251-254.
- 9. Yarmolenko M. V. Enhanced Diffusion and Other Phenomena during Rapid Heating of Bimetals: Theory and Experiments / M. V. Yarmolenko // Defect and Diffusion Forum. 1997. Vols. 143-147. P. 1613-1618.
- 10. Ярмоленко М. В. Об эффекте сглаживания поверхности при росте интерметаллида между матрицей и покрытием / М. В. Ярмоленко, К. П. Гуров, А. М. Гусак // Физика и химия обработки материалов. 1989. №4. С.138 140.
- 11. Ярмоленко М. В. Влияние внутренних напряжений на диффузионный рост фаз в образцах цилиндрической формы / В. В. Богданов, Л. Н. Парицкая, М. В. Ярмоленко // Металлофизика. 1990. Т.12, №5. С. 98 104.

References:

- 1. Yarmolenko M. V. The Kirkendall Effect and Phase Formation Kinetics during Solid State Reactions / M.V.Yarmolenko // Scientific review. 2018. №1 (44). C. 42 52.
- 2. Yarmolenko M. V. Constancy of the Flow in a Growing Intermetallic Layer Under Conditions of Interdiffusion / K. P. Gurov, A. M. Gusak, M. V. Yarmolenko // Metallofizika. 1988. V. 10. №. 5. C. 91-92.
- 3. Yarmolenko M. V. A simple way of describing the diffusion phase growth in cylindrical and spherical samples / A. M. Gusak, M. V. Yarmolenko // Journal of Applied Physics. 1993. Vol.73, №10. P. 4881-4884.
- 4. Yarmolenko M. V. Osobennosti diffuzionnogo rosta faz v obraztsakh tsilindricheskoy formy / V. V. Bogdanov, A. M. Gusak, L. N. Paritskaya, M. V. Yarmolenko // Metallofizika. 1990. 12(3). P. 60 66.
- 5. Yarmolenko M. V. A model of growth of an intermediate phase in biand polycrystals / M. V. Yarmolenko, A. M. Gusak, K. P. Gurov // Journal of Engineering Physics and Thermophysics. 1993. 65(3). P. 876 881.
- 6. Yarmolenko M. V. Describing the Diffusion Phase Growth in Polycrystals: Analytical Solution / M. V. Yarmolenko // Defect and Diffusion Forum. 1997. Vols. 143-147. P. 1567-1572.
- 7. Yarmolenko M. V. The Kirkendall Effect: Analytical Solution and Monte Carlo Modeling / M.V. Yarmolenko // Defect and Diffusion Forum. 1997. Vols. 143-147. P. 509-514.
- 8. Yarmolenko M.V. Grain Boundary Diffusion Parameters Determination using A-Kinetics of Intermetallic Layer Formation / M.V.Yarmolenko // Solid State Phenomena. 2000. Vol.72. P.251-254.
- 9. Yarmolenko M. V. Enhanced Diffusion and Other Phenomena during Rapid Heating of Bimetals: Theory and Experiments / M. V. Yarmolenko // Defect and Diffusion Forum. 1997. Vols. 143-147. P. 1613-1618.

- 10. Yarmolenko M. V. On the Effect of Surface Smoothing During Growth of Intermetallides Between Substrate and Coating / M. V. Yarmolenko, K. P. Gurov, A. M. Gusak // Fizika i Khimiya Obrabotki Materialov.- 1989. №4. P. 138 140.
- 11. Yarmolenko M. V. Effect of Internal Stresses on Diffusion Phase Growth in Cylindrical Specimens / V. V. Bogdanov, L. N. Paritskaya, M. V. Yarmolenko// Metallofizika. 1990. T.12, №5. C. 98 104.